Opto Isolators



RS-232 to RS-232 Optical Isolators

Model 590 Series

Why let ground loops disrupt your asynchronous RS-232 or RS-422/485 communications?

Data Rate Selection

0-19.2 or 0-115.2 kbps

Interface Isolation Options

RS-232 or RS-422/485 interfaces

Choice of Signal Isolation

Various combinations for signal protection

Self-Powered

DC or AC power, depending on model

Many Model Options

Choose from various combinations of signal protection, interfaces, data rates and connectors

to RS-232 optical isolators guards your asynchronous equipment from the hazards of ground looping. Plugging directly into your DTE hardware, the Model 590 Series provides 2500V RMS peak DCE/DTE isolation.

Both the Model 590A (19.2 kbps max) and Model 591A (115.2kbps max) isolate 4 lines on the RS-232 interface--two of which are selectable by internal jumpers.

The Model 592 (19.2 kbps max) and Model 594 (115.2kbps max) isolate 7 pre-wired lines on the RS-232 interface.

For more information, visit www.patton.com.



Specifications

Transmission Format

Asynchronous, full or half duplex

Interface Standard

EIA RS-232-E

Connectors

(2) DB-25 Female

Data Rates

Up to 19,200 bps (Model 590A); Up to 115.200 bps(Model 591A)

Isolation

2500VRMS

Power Supply

Interface Powered; Optional power supplied to pin 9 (either side) at +5V DC ±5% @ 10mA

Compliance

89/336/EEC, FCC Part 15, CLASS A

Dimensions

3.8"L x 2.1"W x 0.79"H (9.7 x 5.3 x 2.0 cm)

Temperature Range

0-50°C (32-122°F)

Altitude

Up to 10,100 feet

Weight

5.7 oz. (161.6g)

Humidity

5 to 95% non-condensing

Selection Chart

Patton Model	Interface	Connectors	Async Data Rates	Signals Isolated	Isolation (VRMS)	Power Supply
590A	RS-232	DB-25F	0-19.2 kbps	TD, RD, + one control signal in each direction	2500	Interface Powered (optional DC power to pin 9)
591A	RS-232	DB-25F	0-115.2 kbps	TD, RD, + one control signal in each direction	2500	Interface Powered (optional DC power to pin 9)
592	RS-232	DB-25F	0-19.2 kbps	TD, RD, RTS, CD, CTS, DSR, DTR	2500	External AC Adapter
593/25F	RS-422 /485	DB-25F	0-115.2 kbps	TD+, TD-, RD+, RD-	2500	AC Adpater (Regulated)
593/45	RS-422 /485	RJ-45	0-115.2 kbps	TD+, TD-, RD+, RD-	2500	AC Adpater (Regulated)
593/TB	RS-422 /485	Terminal Blocks	0-115.2 kbps	TD+, TD-, RD+, RD-	2500	AC Adpater (Regulated)
594	RS-232	DB-25F	0-115.2 kbps	TD, RD, RTS, CD, CTS, DSR, DTR	2500	External AC Adapter





Network Access & Connectivity Solutions for Enterprise, Carrier & Industrial Applications





7622 Rickenbacker Drive ● Gaithersburg, MD 20879 ● +1 301.975.1000 ● www.patton.com ● sales@patton.com

PE-Inalp Networks Private Ltd

An Associate of

PATTUR®

Old No. 14 and New No.6, Brahadambal Road, Nungambakkam High Road Chennai: 600 034, India Phone +91 44 45490395/6/7 Fax +91 44 4549.0394 Email sales@patton.co.in Web www.patton.co.in Patton-Inalp Networks AG



Meriedweg 7 CH-3172 Niederwangen Switzerland Phone **+41 (31) 985 25 25** Fax **+41 (31) 985 25 26**

Phone **+41 (31) 985 25 25**Fax **+41 (31) 985 25 26**E-mail **sales@inalp.com**Web **www.inalp.com**

Patton Electronics Co.



7622 Rickenbacker Drive Gaithersburg, Maryland 20879

Phone +1 301 975 1000 Fax +1 301 869 9293 E-mail sales@patton.com Web www.patton.com

07M590-DS2