

# IpChannel Bank Multi-Port FXS or FXO Gateway

## SmartNode™ 4300 Series



*The IpChannel Bank is the perfect VoIP gateway for applications requiring up to 32 concurrent analog voice/fax calls within a single redundant solution.*

### Up to 32 FXS or FXO

*Simultaneous voice or fax calls on all ports. Advanced local call switching.*

### Full SIP and T.38 support

*Supports the complete range of industry standard VoIP: SIP, H.323, T.38 fax, fax and modem bypass, DTMF relay. Codecs G.729, G.723 etc.*

### Outstanding Interoperability

*Interoperable for voice and T.38 fax with leading SIP service providers, soft-switch vendors and Asterisk™ IP-PBX.*

### SmartNode™ Awards

- **2010 Internet Telephony Product of the Year:** SmartNode™ 5400
- **2009 Internet Telephony Product of the Year:** SmartNode™ 4400 Series
- **2008 Internet Telephony Product of the Year:** SmartNode™ 4961
- **2007 Internet Telephony Product of the Year:** SmartNode™ S-DTA
- **2006 Internet Telephony Product of the Year:** SmartNode™ 4960
- **2005 Internet Telephony Product of the Year:** SmartNode™ 4630

The SmartNode 4300 Series IpChannel Bank is the perfect business solution for applications requiring up to 32 concurrent analog voice/fax calls. The IpChannel Bank transforms any PBX system, analog call-center application, or ISP MDU service into a state-of-the-art packet-voice system without requiring costly equipment replacement or upgrades.

The models in the SN4300 Series are available with up to 32 FXS or FXO ports. The SN4300 Series supports key industry-standard VoIP signaling protocols such as SIP, H.323, and T.38 Fax Relay—plus fax-bypass and modem-bypass. This ensures interoperability with the leading soft switches and VoIP services.


The SN4300 runs SmartWare™, the award-winning VoIP real-time operating system

used in all SmartNode products. The versatile VoIP gateway software enables the SN4300 to talk with up to 8 VoIP servers using SIP and H.232 protocols.


With Telephony-over-IP (ToIP) call switching, calls can automatically select the least-cost-route while providing flexible numbering plans and end-to-end feature transparency. PPPoE, DHCP, and VLAN offers universal IP connectivity and optional IPsec VPN with AES/3DES guarantees secure voice over the public network.

Offering easy setup, reliable operation, and third-party interoperability on a proven platform, the SN4300 Series IpChannel Bank sits at the core of cost-effective business solutions. The investment protection you need for the future is here today.

Visit [www.patton.com](http://www.patton.com) for more information.



## Typical applications



## Specifications\*

### Capacity

16, 24, 32 simultaneous VoIP calls

### Data Services

Onw 10/100 Ethernet port • Complete IP access router • DHCP Client & server • Packet fragmentation • NATP RFC 1631 access control lists

### Quality of Service

DownStreamQoS™ • IEEE 802.1p, TOS, DiffServ labeling • IEEE 802.1Q, VLAN tag insertion/deletion (4096 VLAN IDs, multiple VLAN support

### Management

Web/HTTP, CLI with local console and remote Telnet access • TFTP configuration & firmware loading • SNMP MIB II and product MIB • Secure autoprovisioning for both firmware and unit/sub-

scriber configuration • Built-in diagnostic tools (trace, debug, call generator)

### FXS Connectivity

2-wire Loopstart on 50 pin (12 to 24 channels) or 64 pin (32 channels) Telco connector • Short haul loop 1.1 km @3REN • EuroPOTS (ETSI EG201188) • Programmable AC impedance, feeding, ring and on-hook voltage • Caller-ID FSK and ITU V.23/Bell 202 generation

### FXO Connectivity

2-wire Loopstart on 50pin (12 to 24 channels) or 64-pin (32 channels) Telco connector • Programmable impedance, ring detection, tone detection, disconnect supervision • Caller ID detection

### Voice Signaling

SIPv2 H.323v4 (simultaneously with B2BUA capability) • SIP call transfer, redirect • DTMF in-band & out-of-band •

All tones programmable (dial, ringing, busy)

### Call Switching and Services

Regular expression based call routing and number manipulation • Number blocking • Short-dialing • Digit collection, distribution and hunt groups • transparent line extension

### Voice Processing

Codec G.711 a-law/mu-law, G.723, G.729ab • G.726, G.727. T.38 fax relay • G.711 transparent fax and bypass

### System

CPU Motorola MPC875 @ 133 MHz • Memory 32 MB SDRAM/8 MB Flash

### Dimensions

19-in. rack-mount chassis  
48.3W x 4.44H x 30.50D cm

### Weight

4.1 kg

### Power

100-240 VAC (50/60 Hz) • Power dissipation: > 22W (60W max, model SN4432/JS/RUI)

### Temperature

32-104°F (0-40°C)

### Humidity

5-80% (non condensing)

### Compliance

EMC compliance: EN 55022 and EN 55024 • Safety compliance: EN 50950 • CE compliance • FCC Part 15 Class A • RoHS

\* Specifications subject to change without notice.

**PATTON**  
*Let's Connect!*

**Patton Electronics Co.**  
7622 Rickenbacker Drive  
Gaithersburg, Maryland 20879  
USA  
Phone +1 301 975 1000  
Fax +1 301 869 9293  
E-mail [sales@patton.com](mailto:sales@patton.com)  
Web [www.patton.com](http://www.patton.com)

**PE-Inalp Networks Private Ltd**  
Old No. 14 and New No.6,  
Brahadambal Road,  
Nungambakkam High Road  
Chennai: 600 034, India  
Phone +91 44 45490395/6/7  
Fax +91 44 4549.0394  
Email [sales@patton.co.in](mailto:sales@patton.co.in)  
Web [www.patton.co.in](http://www.patton.co.in)

**Patton-Inalp Networks AG**  
Meriedweg 7  
CH-3172 Niederwangen  
Switzerland  
Phone +41 (31) 985 25 25  
Fax +41 (31) 985 25 26  
E-mail [sales@inalp.com](mailto:sales@inalp.com)  
Web [www.inalp.com](http://www.inalp.com)

07MSN4300-DS5

Patton is a registered trademark, and is a trademark of Patton Electronics Company in the United States and other countries.