

USER MANUAL

MODEL 537 Token Ring Surge Protector



PATTON
Electronics Co.



An ISO-9001
Certified Company

Part# 07M537-A
Doc# 074180U,
Rev. B
Revised 1/22/08

SALES OFFICE
(301) 975-1000
TECHNICAL SUPPORT
(301) 975-1007
<http://www.patton.com>

1.0 WARRANTY

Patton Electronics warrants all Model 537 components to be free from defects, and will—at our option—repair or replace the product should it fail within one year from the first date of shipment. This warranty is limited to defects in workmanship or materials, and does not cover customer damage, abuse or unauthorized modification. If this product fails or does not perform as warranted, your sole recourse shall be repair or replacement as described above. Under no condition shall **Patton Electronics** be liable for any damages incurred by the use of this product. These damages include, but are not limited to, the following: lost profits, lost savings and incidental or consequential damages arising from the use of or inability to use this product. **Patton Electronics** specifically disclaims all other warranties, expressed or implied, and the installation or use of this product shall be deemed an acceptance of these terms by the user.

1.2 SERVICE

All warranty and nonwarranty repairs must be returned freight prepaid and insured to Patton Electronics. All returns must have a Return Materials Authorization number on the outside of the shipping container. This number may be obtained from Patton Electronics Technical Support: **(301) 975-1007**; <http://www.patton.com>; or, support@patton.com.

Notice: Packages received without an RMA number will not be accepted.

Patton Electronics' technical staff is also available to answer any questions that might arise concerning the installation or use of your Patton Model 537 Surge Protector. Technical Service hours: **8AM to 5PM EST, Monday through Friday.**

1.3 CE NOTICE

The CE symbol on your Patton Electronics equipment indicates that it is in compliance with the Electromagnetic Compatibility (EMC) directive and the Low Voltage Directive (LVD) of the Union European (EU). A Certificate of Compliance is available by contacting Technical Support.

2.0 GENERAL INFORMATION

Thank you for your purchase of this Patton Electronics product. This product has been thoroughly inspected and tested and is warranted for One Year parts and labor. If any questions arise during installation or use of the unit, contact Patton Electronics Technical Support: (301) 975-1007; <http://www.patton.com>; or, support@patton.com.

3.0 PRODUCT DESCRIPTION

The Patton Model 537 Surge Protector uses a solid state hybrid network to guard token ring ports against data loss and hardware damage due to transient surges. The Model 537 inserts between the data cable and a token ring port. It intercepts data line transients and sends them directly to chassis ground through the connector shield.

Warning: This product will not provide complete protection should your equipment or building be subject to a direct lightning hit.

4.0 SURGE PROTECTION BENEFITS

The method of surge protection used in the Model 537 adds four benefits to your system:

High Surge Capacity The Model 537 handles up to 1500 Watts of surge energy without failure.

Quick Response The Model 537 has fast response times (1 pS at the component level; 0.5 μ S installed). Transient surges are clamped at 9 volts.

Low Impedance The Model 537 adds minimal load to your system. It is about the same as a gender changer.

Open Failure The Model 537 fails "open" if your system experiences a severe transient or power fault above the rated voltage of the protector. This means that data and surge energy is shunted directly to chassis ground, rather than being allowed to flow throughout the system.

5.0 INSTALLATION

The Patton Model 537 is simple to install and requires no user configuration. Follow these installation steps.

1. Disconnect the data cable from the device you are protecting in a manner consistent with the manufacturer's installation instructions.
2. Be sure the connector shield on the device you are protecting is connected to frame ground. If not, contact Patton Technical Support for further instructions.
3. Plug the connector of the Model 537 **directly** into the Token Ring port of the device you are protecting.
4. Re-attach the cable to the available connector on the Model 537. The Model 537 is now inserted between the data port and the data cable, and will provide up to 1500 Watts of protection to the data port.

Note: We recommend that a Patton surge protector be connected to the other end of the data cable as well. To order, please contact us at: **(301) 975-1000**; **<http://www.patton.com>**; or, **support@patton.com**

APPENDIX A

PATTON MODEL 537 SPECIFICATIONS

Surge Capacity:	1500 Watts for 1msec 400A with a $8/20\mu\text{S}$ pulse
Connectors:	Two IBM data style connectors
Lines Protected:	All four on the IBM data connector
Compliance:	CE marked for EMC directive 89\336\EEC (ESD.EFT)
Clamping Voltage:	9.0 Volts in 500nsec
Protection Mode:	All lines common mode to connector shield. All lines differential.

Copyright ©
Patton Electronics Company
All Rights Reserved

Dear Valued Customer,

Thank you for purchasing Patton Electronics products! We do appreciate your business. I trust that you find this user manual helpful.

We manufacture one of the widest selections of data communications products in the world including CSU/DSU's, network termination units, powered and self-powered short range modems, fiber optic modems, interface converters, baluns, electronic data switches, data-line surge protectors, multiplexers, transceivers, hubs, print servers and much more. We produce these products at our Gaithersburg, MD, USA, facility, and can custom manufacture products for your unique needs.

We would like to hear from you. Please contact us in any of the following ways to tell us how you like this product and how we can meet your product needs today and in the future.

Web:	http://www.patton.com
Sales E-mail:	sales@patton.com
Support E-mail:	support@patton.com
Phone - Sales	(301) 975-1000
Phone - Support	(301) 975-1007
Fax:	(301) 869-9293
Mail:	Patton Electronics Company 7622 Rickenbacker Drive Gaithersburg, MD 20879 USA

We are committed to a quality product at a quality price. Patton Electronics is ISO 9001 certified. We meet and exceed the highest standards in the industry (CE, UL, etc.).

Please contact us and let us know how we may provide you with the answers to your needs.

Thank you.

Burton A.Patton
Vice President

P.S. Please tell us where you purchased this product.
