

Technote #
100018

Distance Table for SRM Models 1004A/1008

Date
November 11, 1998

Distance Table for SRM Models 1004A & 1008.

Data Rate	Distance in Miles (km) for Wire Gauge			
kbps	19 (0.9mm)	22 (0.6mm)	24 (0.5mm)	26 (0.4mm)
1.2	9.0 (14.6)	6.5 (10.5)	5.0 (8.1)	3.9 (6.3)
9.6	7.1 (11.5)	4.6 (7.5)	3.5 (5.7)	2.8 (4.5)
38.4	5.0 (8.1)	2.9 (4.7)	2.2 (3.5)	1.5 (2.4)
115.2	3.5 (5.6)	2.6 (4.2)	1.4 (2.3)	0.9 (1.5)

100018|^Distance Table for SRM Models 1004A/1008|^November 11, 1998|^Distance Table for SRM Models 1004A & 1008.

Data Rate	Distance in Miles (km) for Wire Gauge			
kbps	19 (0.9mm)	22 (0.6mm)	24 (0.5mm)	26 (0.4mm)
1.2	9.0 (14.6)	6.5 (10.5)	5.0 (8.1)	3.9 (6.3)
9.6	7.1 (11.5)	4.6 (7.5)	3.5 (5.7)	2.8 (4.5)
38.4	5.0 (8.1)	2.9 (4.7)	2.2 (3.5)	1.5 (2.4)
115.2	3.5 (5.6)	2.6 (4.2)	1.4 (2.3)	0.9 (1.5)

^Submit New Technote|^

PATTON ELECTRONICS CO. TECHNICAL SUPPORT