

Technote #
100026

2703: Updated Clocking Configuration.

Date
May 11, 1999

Model 2703: Regarding the User Manual (Revised 6/19/1998).

Here are updates on pages 5 & 7 of the user manual.

On "S1 Summary Table" (page 5),
change the row for S1-1 as follows:

Position	Function	Factory Default
S1-1	X.21/EIA-530/V.35	off (V.35)

In Section "3.1.2 Switch Set S2 (To Be Used in Conjunction
with S1-1" (page 7),
change the description table as follows:

S2-1	S2-2	Setting
ON	ON	V.35 Interface (S1-1 must be "off").
off	off	X.21/EIA-530 Interface (See S1-1).

----- 100026|^2703: Updated Clocking Configuration.|^May 11, 1999|^Model 2703: Regarding the User Manual (Revised 6/19/1998).

Here are updates on pages 5 & 7 of the user manual.

On "S1 Summary Table" (page 5),
change the row for S1-1 as follows:

Position	Function	Factory Default
S1-1	X.21/EIA-530/V.35	off (V.35)

In Section "3.1.2 Switch Set S2 (To Be Used in Conjunction
with S1-1" (page 7),
change the description table as follows:

S2-1	S2-2	Setting
ON	ON	V.35 Interface (S1-1 must be "off").
off	off	X.21/EIA-530 Interface (See S1-1).

-----|^Submit New Technote|^

PATTON ELECTRONICS CO. TECHNICAL SUPPORT