



April 16, 2015

Greetings,

BroadSoft is pleased to announce that the Patton SmartNode Trinity SBC has been formally validated with BroadWorks. The device model(s) listed below have been validated as interoperable with the BroadWorks SIP interface. Configuration details and any issues or limitations identified during the interoperability testing are documented in the BroadSoft Partner Configuration Guide (PCG) *PartnerConfigGuide Patton SmartNode Trinity SBC*. The PCG is available to BroadSoft customers on the BroadSoft Xchange website at [xchange.broadsoft.com](http://xchange.broadsoft.com).

BroadSoft validates that the device interoperates with the BroadWorks SIP interface. BroadSoft does not validate qualitative aspects of the device, capacity, or other device capabilities outside the scope of the SIP signaling interface.

The validation covers the Patton version(s) and BroadWorks releases listed below. Other versions tested previously are documented in the PCG.

Patton SmartNode Trinity version Trinity 3.x \*  
BroadWorks Release 20.0 / 20.sp1

\*This validation also applies to all subsequent compatible maintenance releases to this device version.

Best Regards,

A handwritten signature in black ink that reads 'Wesley Hacker'.

Wesley Hacker  
Director, Solutions Engineering  
+1.240.364.5149  
[wesley@broadsoft.com](mailto:wesley@broadsoft.com)