

Bulletin number: SN-2007-07-01

Issue: 1.1

Date: July 2007



Patton Electronics Company, Inc.

7622 Rickenbacker Drive

Gaithersburg, MD 20879 USA

Tel. +1 (301) 975-1000

Fax +1 (301) 869-9293

support@patton.com

http://www.patton.com

End of Life Notice

SmartNode 1200, 1400, 2300, 2400

Introduction

This End of Life (EOL) notice involves the Manufacture Discontinue (MD) and EOL of the SmartNode models 1200, 1400, 2300, 2400 and derivative models. These modems are being discontinued as a result of aging hardware technology, the unavailability of component parts and the introduction of next generation products with higher performance at lower cost.

Milestones

Milestone	Definition	Date
End-of-Life Announcement date	The date the document that announces the end of sale and end of life of a product is distributed to the general public.	July 30, 2007
End-of-sale date	The last date to order the product from Patton Electronics. The product is no longer for sale after this date.	August 30, 2007
Last shipment date	The last-possible ship date that can be requested of Patton Electronics. Actual ship date is dependent on lead-time.	December 30, 2007
Last date of support	The last date to receive service and support for the product. After this date, all support services for the product are unavailable, and the product becomes obsolete.	December 30, 2008

The availability of software maintenance releases is governed by the [SmartWare Software Release Concept](#). R3.20 is the last release running on SmartNode 1200, 1400 and 2300; R4.2 the last release running on SmartNode 2400.

Models Affected

Model	Description	Replacement product
SN1200/2VIL/UI	Smartnode Dual BRI VoIP GW-Router, 2 x 10baseT, 2 VoIP channels. Includes SNSW-IPR1. Internal UI Power	SN4552/2BIS/EUI
SN1200/2VL/UI	Smartnode Dual BRI VoIP Gateway, 2 x 10baseT, 2 VoIP channels. Internal UI Power	SN4552/2BIS/EUI
SN1400/4VIL/UI	Smartnode Dual BRI VoIP GW-Router, 2 x 10baseT, 4 VoIP channels, Includes SNSW-IPR1,	SN4634/3BIS/UI

	Internal UI Power	
SN1400/4VL/UI	Smartnode Dual BRI VoIP Gateway, 2 x 10baseT, 4 VoIP channels. Internal UI Power	SN4634/3BIS/UI
SN2300/0V/UI	Smartnode VoIP Gateway, 1x10baseT, 1x10/100baseT, X.21/V.35, 3 slots for voice interface cards, Internal UI power	n/a
SN2300/0VI/UI	Smartnode VoIP GW-Router;1x10baseT, 1x10/100baseT, X.21/V.35, 3 slots for voice interface cards, Internal UI Power.	n/a
SN2300/12FXSIL/UI	Smartnode 12 FXS VoIP GW-Router, 1x10baseT, 1x10/100baseT, X.21/V.35, Line Power (3 SN-IC4FXS and 1 SN-PM-48V-INT installed), Internal UI power	SN4912/JS/RUI
SN2300/1E14FXSIL/UI	Smartnode 1 E1/PRI VoIP GW-Router, 1x10baseT, 1x10/100baseT, X.21/V.35, 4 FXS ports (1 SN-ICE1V, 1 SN-IC4FXS and 1 SN-PM-48V-INT installed), Internal UI Power.	SN4960/1E30V/UI plus SN4114/JS/EUI
SN2300/1E1IL/UI	Smartnode 1 E1/PRI VoIP GW-Router, 1x10baseT, 1x10/100baseT, X.21/V.35, (1 SN-ICE1V installed). Internal UI power.	SN4960/1E30V/UI
SN2300/1E1L/UI	Smartnode 1 E1/PRI VoIP Gateway, 1x10baseT, 1x10/100baseT, X.21/V.35, (1 SN-ICE1V installed), Internal UI Power	SN4960/1E30V/UI
SN2300/1T14FXSIL/UI	Smartnode 1 T1/PRI VoIP GW-Router, 1x10baseT, 1x10/100baseT, X.21/V.35, 4 FXS VoIP ports (1 SN-ICT1V, 1 SN-IC4FXS and 1 SN-PM-48V-INT installed), Internal UI Power.	SN4960/1E24V/UI plus SN4114/JS/EUI
SN2300/1T1IL/UI	Smartnode 1 T1/PRI VoIP GW-Router, 1x10baseT, 1x10/100baseT, X.21/V.35, 1 SN-ICT1V installed, Internal UI power.	SN4960/1E24V/UI
SN2300/1T1L/UI	Smartnode 1 T1/PRI VoIP Gateway, 1x10baseT, 1x10/100baseT, X.21/V.35, 1 SN-ICT1V installed, Internal UI power.	SN4960/1E24V/UI
SN2300/2E1IL/UI	Smartnode 2 E1/PRI VoIP GW-Router, 1x10baseT, 1x10/100baseT, X.21/V.35, 2 SN-ICE1V installed, Internal UI power.	SN4960/4E60V/UI
SN2300/2E1L/UI	Smartnode 2 E1/PRI VoIP Gateway, 1x10baseT, 1x10/100baseT, X.21/V.35, 2 SN-ICE1V installed, Internal UI power.	SN4960/4E60V/UI
SN2300/2T1IL/UI	Smartnode 2 T1/PRI VoIP GW-Router, 1x10baseT, 1x10/100baseT, X.21/V.35, 2 SN-ICT1V installed, Internal UI power.	SN4960/4E48V/UI
SN2300/2T1L/UI	Smartnode 2 T1/PRI VoIP Gateway, 1x10baseT, 1x10/100baseT, X.21/V.35, 2 SN-ICT1V installed, Internal UI power.	SN4960/4E48V/UI

SN2300/4BRV4FXSIL/UI	Smartnode 4 BRI & 4 FXS VoIP GW-Router, 1x10baseT, 1x10/100baseT, X.21/V.35, (1 SN-IC4BRV, 1 SN-IC4FXS and 1 SN-PM-48V-INT installed), Internal UI Power	SN4638/5BIS/UI plus SN4114/JS/EUI
SN2300/4BRVIL/UI	Smartnode 4 BRI VoIP GW-Router, 1x10baseT, 1x10/100baseT, X.21/V.35, Line Power (1 SN-IC4BRV-8V and 1 SN-PM-48V-INT installed), Internal UI Power.	SN4638/5BIS/UI
SN2300/4FXSIL/UI	Smartnode 4 FXS VoIP GW-Router, 1x10baseT, 1x10/100baseT, X.21/V.35, Line Power (1 SN-IC4FXS and 1 SN-PM-48V-INT installed), Internal UI Power.	SN4524/JS/EUI (SN4834/JSC/EUI with V.35)
SN2300/8BRVIL/UI	Smartnode 8 BRI VoIP GW-Router, 1x10baseT, 1x10/100baseT, X.21/V.35, Line Power (2 SN-IC4BRV-8V and 1 SN-PM-48V-INT installed), Internal UI Power.	2x SN4638/5BIS/UI
SN2300/8FXSIL/UI	Smartnode 8 FXS VoIP GW-Router, 1x10baseT, 1x10/100baseT, X.21/V.35, Line Power (2 SN-IC4FXS and 1 SN-PM-48V-INT installed), Internal UI Power.	SN4528/JS/EUI (SN4838/JSC/EUI with V.35)
SN2400/0V/48	Modular Smartnode VoIP Gateway, 4 slots for voice interface cards, 2x10/100baseT, 48V DC Power Supply.	n/a
SN2400/0V/UI	Modular Smartnode VoIP Gateway, 4 slots for voice interface cards, 2x10/100baseT, Internal UI Power.	n/a
SN2400/0VI/48X	Smartnode VoIP GW-Router, 4 slots for voice interface cards, 2x20/100baseT, 48V DC Power Supply.	n/a
SN2400/0VI/UI	Modular Smartnode VoIP GW-Router, 4 slots for voice interface cards, 2x10/100baseT, Internal UI Power.	n/a
SN2400/12FXSIL/UI	Smartnode 12 FXS VoIP GW-Router, 2x10/100baseT, (3 SN-4FXS installed and 1 SN-PM-40V-INT installed), Internal UI Power.	SN4912/JS/RUI
SN2400/16BRVIL/UI	Smartnode 16 BRI So VoIP GW-Router, 2x10/100baseT, (4 SN-IC4BRV and 1 SN-PM-40V-INT installed), Internal UI Power.	4xSN4638/5BIS/UI
SN2400/16FXSIL/UI	Smartnode 16 FXS VoIP GW-Router, 2x10/100baseT, (4 SN-IC4FXS installed and 1 SN-PM-40V-INT installed), Internal UI Power.	SN4916/JS/RUI
SN2400/1E1IL/UI	Smartnode 1 E1/PRI VoIP GW-Router, 2x10/100baseT, (1 SN-ICE1V installed), Internal UI Power.	SN4960/1E30V/UI
SN2400/1E1L/UI	Smartnode 1 E1/PRI VoIP Gateway, 2x10/100baseT, (1 SN-ICE1V installed). Internal UI Power.	SN4960/1E30V/UI

SN2400/1T1IL/UI	Smartnode 1 T1/PRI VoIP GW-Router, 2x10/100baseT, (1 SN-ICT1V installed). Internal UI Power.	SN4960/1E24V/UI
SN2400/1T1L/UI	Smartnode 1 T1/PRI VoIP Gateway, 2x10/100baseT, (1 SN-ICT1V installed). Internal UI Power.	SN4960/1E24V/UI
SN2400/2E1IL/UI	Smartnode 2 E1/PRI VoIP GW-Router, 2x10/100baseT, (2 SN-ICE1V installed), Internal UI Power.	SN4960/4E60V/UI
SN2400/2E1L/UI	Smartnode 2 E1/PRI VoIP Gateway, 2x10/100baseT, (2 SN-ICE1V installed). Internal UI Power.	SN4960/4E60V/UI
SN2400/2T1IL/UI	Smartnode 2 T1/PRI VoIP GW-Router, 2x10/100baseT, (2 SN-ICT1V installed). Internal UI Power.	SN4960/4E48V/UI
SN2400/2T1L/UI	Smartnode 2 T1/PRI VoIP Gateway, 2x10/100baseT, (2 SN-ICT1V installed). Internal UI Power.	SN4960/4E48V/UI
SN2400/3E1IL/UI	Smartnode 3 E1/PRI VoIP GW-Router, 2x10/100baseT, (3 SN-ICE1V installed), Internal UI Power.	SN4960/4E96V/UI
SN2400/3E1L/UI	Smartnode 3 E1/PRI VoIP Gateway, 2x10/100baseT, (3 SN-ICE1V installed), Internal UI Power.	SN4960/4E96V/UI
SN2400/3T1IL/UI	Smartnode 3 T1/PRI VoIP GW-Router, 2x10/100baseT, (3 SN-ICT1V installed). Internal UI Power.	SN4960/4E96V/UI
SN2400/3T1L/UI	Smartnode 3 T1/PRI VoIP Gateway, 2x10/100baseT, (3 SN-ICT1V installed), Internal UI Power.	SN4960/4E96V/UI
SN2400/4BRV1E11E0IL/UI	Smartnode 4 BRI VoIP GW-Router, 2x10/100baseT, (1 SN-IC4BRV & 1 SN-IC-E1V-0 & 1 SN-IC-E1V installed), Internal UI Power.	SN4960/4E30V/UI plus SN4638/5BIS/UI
SN2400/4E1IL/UI	Smartnode 4 E1/PRI VoIP GW-Router, 2x10/100baseT, (4 SN-ICE1V installed), Internal UI Power.	SN4960/4E120V/UI
SN2400/4E1L/UI	Smartnode 4 E1/PRI VoIP Gateway, 2x10/100baseT, (4 SN-ICE1V installed), Internal UI Power.	SN4960/4E120V/UI
SN2400/4T1IL/UI	Smartnode 4 T1/PRI VoIP GW-Router, 2x10/100baseT, (4 SN-ICT1V installed), Internal UI Power.	SN4960/4E96V/UI
SN2400/4T1L/UI	Smartnode 4 T1/PRI VoIP Gateway, 2x10/100baseT, (4 SN-ICT1V installed), Internal UI Power.	SN4960/4E96V/UI
SN2400/8BRVIL/UI	Modular Smartnode 8 BRI VoIP GW-Router, 2x10/100baseT, (2 SN-IC4BRV and 1 SN-PM-40V-INT installed), Internal UI Power.	2x SN4638/5BIS/UI



Additional Information

For additional help or any questions, please contact your local account representative.

http://www.patton.com/company/contact_us.asp